

# NIBTORQUE

## THE ELIMINATOR HYDRAULIC CHAIN POWERED WRENCH

**THE ELIMINATOR®  
ELIMINATES  
WORKSITE INJURY**



A VERY SAFE, HYDRAULIC OR ELECTRIC POWERED, PORTABLE MAKE-UP/BREAK OUT CHAIN PIPE WRENCH SYSTEM. QUICK AND EASY HOOK UP TO HANDLE YOUR TOUGHEST CONNECTIONS WITH EASE, AND CONTROL

### GENERAL SPECIFICATIONS

THE ULTIMATE IN SAFETY AND CONTROL TO MAKE-UP OR BREAK-OUT YOUR TOUGHEST CONNECTIONS  
MAXIMUM TORQUE ADJUSTMENT IS HYDRAULICALLY CONTROLLED FOR ACCURATE TORQUE SETTING  
FAST AND EASY HOOK UP (FOR EASIEST OPERATION USE BACK HOE OR LIFTING MACHINE)  
EACH MACHINE HAS A BROAD RANGE OF PIPE DIAMETERS IT CAN ACCEPT

### HYDRAULIC PUMP OPTIONS

HAND POWERED PUMP

12V DC HYDRAULIC PUMP

AC POWERED ELECTRIC PUMP (OPTIONALLY ORDERED IN 115V, 220V, 240V)

*PUMP INCLUDES 20 FT HYDRAULIC HOSES*



**ELECTRIC PUMP**



**DC POWERED PUMP**



**HAND PUMP**

• Allentown, Pa, 18104

Fax Toll Free: • Phone: 484.539.9022 • Toll Free Fax: 866.780.9316

Email: [bolting@nibtorque.com](mailto:bolting@nibtorque.com) • Web: [www.NIBTORQUE.com](http://www.NIBTORQUE.com)

# NIBTORQUE



## SPECIFICATIONS

MODEL	MAX TORQUE	RANGE	MAX OD	GRIP WIDTH	WT w/ DC PUMP	WRENCH WT	CYL WT	CHAIN WT
2.6	2600 FT LBS	1-5"	6"	4"	210 LBS IN CRATE	12	29	7 3/8
7.5	7500 FT LBS	2 1/4 - 4 7/8	5"	4.44	275 LBS IN CRATE	31	31	13 1/8
15	15000 FT LBS	3 1/4 - 5 1/4	8 1/4	5.0	350 LBS IN CRATE	45	28	13 1/8
20	25000 FT LBS	4 1/4 - 10 3/4	10.75	4.88	650 LBS IN CRATE	74	SPECIAL	20 1/2
50	50000 FT LBS	4 - 8 1/4	14"	7.25	700 LBS IN CRATE	129	52	42
90	90000 FT LBS	4 - 12	24"	9"	1300 LBS IN CRATE	317	77	99
140	140000 FT LBS	6 - 9 1/4	22"	10"	2250 LBS IN CRATE			

GRIP WIDTH IS THE WIDTH THE INDIVIDUAL WRENCH NEEDS TO GRIP ON PIPE

SYSTEM SHIPS IN A WOODEN CRATE. (FUMIGATED STAMPED WOOD AVAILABLE FOR INTERNATIONAL SHIPPING)



• Allentown, Pa, 18104

Fax Toll Free: • Phone: 484.539.9022 • Toll Free Fax: 866.780.9316

Email: [bolting@nibtorque.com](mailto:bolting@nibtorque.com) • Web: [www.NIBTORQUE.com](http://www.NIBTORQUE.com)